

List of Danube Bridges

Vertical bridge clearance refers to the distance (in metres) between the lowest part of the bottom edge of a bridge in the range of the entire width of the fairway channel and the highest navigable water level (HNWL 2010).
Horizontal bridge clearance refers to the width of the fairway channel at low navigable water level (LNWL).

No.	River-km	RB	LB	Name of bridge	Main use	Passageway 1			Passageway 2			HNWL at reference gauge	Notes
						(RB downstream view)			(LB downstream view)				
						Height (m)	Width (m)	Direction	Height (m)	Width (m)	Direction		
The period of reference for the calculation of HNWL and LNWL for the following bridges is 1981-2010													
1	2 414,25	DE	DE	Maximilianbrücke (Kelheim)	Road	5,25	17,25	D + U	--	--	--	540 cm Kelheim	
2	2 412,72	DE	DE	Europabrücke (Kelheim)	Road	6,80	31,10	D + U	--	--	--	540 cm Kelheim	
3	2 410,10	DE	DE	Straßenbrücke Saal	Road	7,10	64,40	D + U	--	--	--	480 cm Oberndorf	Height at crest: 8.22
4	2 401,92	DE	DE	Eisenbahnbrücke Poikam	Rail	7,05	28,75	D + U	--	--	--	Impounded water level Bad Abbach	
5	2 401,74	DE	DE	Wehrbrücke Bad Abbach	Road	6,40	48,45	D + U	--	--	--	Impounded water level Bad Abbach	
6	2 400,28	DE	DE	Wirtschaftswegbrücke Bad Abbach	Road	6,45	48,60	D + U	--	--	--	Impounded water level Bad Abbach	
7	2 387,59	DE	DE	Autobahnbrücke Sinzing	Road	40,80	49,25	D + U	--	--	--	480 cm Oberndorf	
8	2 386,71	DE	DE	Eisenbahnbrücke Sinzing	Rail	10,46	48,65	D + U	--	--	--	480 cm Oberndorf	
9	2 385,67	DE	DE	Eisenbahnbrücke Mariaort	Rail	8,65	32,60	D + U	--	--	--	480 cm Oberndorf	
10	2 381,13	DE	DE	Autobahnbrücke Pfaffenstein (Regensburg)	Road	6,75	35,00	D + U	--	--	--	Impounded water level Regensburg	
11	2 381,04	DE	DE	Wegbrücke Pfaffenstein (Regensburg)	Pedestrian	6,60	37,00	D + U	--	--	--	Impounded water level Regensburg	
12	2 380,17	DE	DE	Oberpfalzbrücke (Regensburg)	Road	6,40	65,00	D + U	--	--	--	Impounded water level Regensburg	Height at crest: 8.16
13	2 379,56	DE	DE	Protzenweiherbrücke (Regensburg)	Road	6,65	12,00	D + U	--	--	--	520 cm Regensburg-Schwabelweis	Height indicator available
14	2 378,39	DE	DE	Nibelungenbrücke (Nordarm, Regensburg)	Road	6,95	50,20	D + U	--	--	--	520 cm Regensburg-Schwabelweis	
15	2 376,82	DE	DE	Eisenbahnbrücke Schwabelweis	Rail	5,95	34,00	D	6,00	33,00	U	520 cm Regensburg-Schwabelweis	Height indicator available
16	2 376,33	DE	DE	Straßenbrücke Regensburg-Schwabelweis	Road	8,65	101,00	D + U	--	--	--	520 cm Regensburg-Schwabelweis	
17	2 369,64	DE	DE	Straßenbrücke Donaustauf	Road	8,75	101,75	D + U	--	--	--	520 cm Regensburg-Schwabelweis	
18	2 358,26	DE	DE	Autobahnbrücke Wörth	Road	8,10	138,45	D + U	--	--	--	520 cm Regensburg-Schwabelweis	
19	2 353,32	DE	DE	Straßenbrücke Pfatter	Road	7,35	85,35	D + U	--	--	--	600 cm Pfatter	Height in recommended channel: 8.05
20	2 321,82	DE	DE	Straßenbrücke UH Schleuse Straubing	Road	8,30	24,00	D + U	--	--	--	505 cm Straubing	
21	2 320,00	DE	DE	Agnes-Bernauer-Brücke (Straubing)	Road	8,85	66,55	D + U	--	--	--	505 cm Straubing	
22	2 316,98	DE	DE	Straßenbrücke Reibersdorf	Road	8,85	71,90	D + U	--	--	--	505 cm Straubing	
23	2 311,27	DE	DE	Eisenbahnbrücke Bogen	Rail	5,00	43,95	D + U	--	--	--	620 cm Pfelling	Height indicator available
24	2 308,40	DE	DE	Straßenbrücke Bogen	Road	9,00	75,10	D + U	--	--	--	620 cm Pfelling	
25	2 290,12	DE	DE	Autobahnbrücke Metten	Road	8,60	71,40	D + U	--	--	--	540 cm Deggendorf	

List of Danube Bridges

Vertical bridge clearance refers to the distance (in metres) between the lowest part of the bottom edge of a bridge in the range of the entire width of the fairway channel and the highest navigable water level (HNWL 2010).
Horizontal bridge clearance refers to the width of the fairway channel at low navigable water level (LNWL).

No.	River-km	RB	LB	Name of bridge	Main use	Passageway 1			Passageway 2			HNWL at reference gauge	Notes
						(RB downstream view)			(LB downstream view)				
						Height (m)	Width (m)	Direction	Height (m)	Width (m)	Direction		
The period of reference for the calculation of HNWL and LNWL for the following bridges is 1981-2010													
26	2 285,89	DE	DE	Eisenbahnbrücke Deggendorf	Rail	8,40	90,00	D + U	--	--	--	540 cm Deggendorf	
27	2 285,87	DE	DE	Wegbrücke Deggendorf	Pedestrian	8,40	90,00	D + U	--	--	--	540 cm Deggendorf	
28	2 285,49	DE	DE	Autobahnbrücke Fischerdorf (Deggendorf)	Road	8,40	89,85	D + U	--	--	--	540 cm Deggendorf	
29	2 284,59	DE	DE	Maximilianbrücke (Deggendorf)	Road	8,60	89,85	D + U	--	--	--	540 cm Deggendorf	
30	2 282,52	DE	DE	Autobahnbrücke Deggenau	Road	9,65	82,90	D + U	--	--	--	540 cm Deggendorf	
31	2 266,23	DE	DE	Donau-Wald-Brücke (Winzer)	Road	8,60	62,00	D + U	--	--	--	480 cm Hofkirchen	
32	2 249,16	DE	DE	Straßenbrücke Vilshofen (Marienbrücke)	Road	8,00	89,00	D + U	--	--	--	480 cm Hofkirchen	
33	2 234,26	DE	DE	Autobahnbrücke Schalding	Road	35,75	100,15	D + U	--	--	--	Impounded water level Kachlet	
34	2 230,63	DE	DE	Kabelsteg Kachlet	Cable	8,50	24,00	D + U	8,50	24,00	D + U	Impounded water level Kachlet	
35	2 230,42	DE	DE	RMD Schleusenbrücke Kachlet	Road	9,40	24,00	D + U	9,40	24,00	D + U	780 cm Passau-Donau	
36	2 230,28	DE	DE	Eisenbahnbrücke Steinbach (Passau)	Rail	6,30	59,20	D + U	--	--	--	780 cm Passau-Donau	Height indicator available
37	2 230,10	DE	DE	Franz-Josef-Strauß-Brücke (Passau)	Road	11,00	67,00	D + U	--	--	--	780 cm Passau-Donau	
38	2 226,96	DE	DE	Schanzlbrücke (Passau)	Road	7,70	101,00	D + U	--	--	--	780 cm Passau-Donau	
39	2 225,75	DE	DE	Luitpoldbrücke (Passau)	Road	5,15	80,55	D + U	--	--	--	780 cm Passau-Donau	Height at crest: 5.95; Height indicator available
40	2 223,28	DE	DE	Eisenbahnbrücke Kräutelstein	Rail	9,50	92,00	D	9,50	71,00	U	780 cm Passau-Donau	
41	2 203,31	DE	DE	Kranbrücke Jochenstein	Crane	7,70	24,00	D + U	7,70	24,00	D + U	Impounded water level Jochenstein	
42	2 194,10	AT	AT	Straßenbrücke Niederranna	Road	8,13	107,30	D + U	--	--	--	281.60 m a. A. Kager-Niederranna	Height at crest: 8.63
43	2 162,92	AT	AT	Fußgängerbrücke Schleuse Aschach	Pedestrian	8,23	24,00	D + U	8,23	24,00	D + U	280.70 m a. A. HW lock Aschach	
44	2 162,68	AT	AT	Schleusenbrücke Aschach	Lock	11,05	24,00	D + U	11,05	24,00	D + U	266.25 m a. A. TW lock Aschach	
45	2 159,97	AT	AT	Straßenbrücke Aschach	Road	8,59	125,00	D + U	--	--	--	265.74 m a. A. Aschach-Agentie	Height at crest: 9.24
46	2 146,73	AT	AT	Schleusenbrücke Ottensheim-Wilhering	Lock	10,70	24,00	D + U	10,70	24,00	D + U	255.97 m a. A. TW lock Ottensheim	
47	2 135,10	AT	AT	Nibelungenbrücke (Linz)	Road	7,96	90,00	D + U	--	--	--	501 cm Linz	Height at crest: 8.18
48	2 133,49	AT	AT	Voest-Bypassbrücke (Linz)	Road	10,01	100,00	D + U	--	--	--	516 cm Linz-Voest-Brücke	
49	2 133,46	AT	AT	Voest-Brücke (Linz)	Road	9,97	100,00	D + U	--	--	--	517 cm Linz-Voest-Brücke	Height at crest: 10.85
50	2 133,42	AT	AT	Voest-Bypassbrücke (Linz)	Road	9,98	100,00	D + U	--	--	--	519 cm Linz-Voest-Brücke	

List of Danube Bridges

Vertical bridge clearance refers to the distance (in metres) between the lowest part of the bottom edge of a bridge in the range of the entire width of the fairway channel and the highest navigable water level (HNWL 2010).
Horizontal bridge clearance refers to the width of the fairway channel at low navigable water level (LNWL).

No.	River-km	RB	LB	Name of bridge	Main use	Passageway 1			Passageway 2			HNWL at reference gauge	Notes
						(RB downstream view)			(LB downstream view)				
						Height (m)	Width (m)	Direction	Height (m)	Width (m)	Direction		
The period of reference for the calculation of HNWL and LNWL for the following bridges is 1981-2010													
51	2 127,73	AT	AT	Straßenbrücke Steyregg	Road	8,36	71,00	D	8,18	70,00	U	251.52 m a. A. Steyregger-Brücke	
52	2 127,68	AT	AT	Eisenbahnbrücke Steyregg	Rail	8,47	67,00	D	8,46	73,80	U	251.52 m a. A. Steyregger-Brücke	
53	2 119,45	AT	AT	Schleusenbrücke Abwinden-Asten	Lock	11,10	24,00	D + U	11,10	24,00	D + U	244.39 m a. A. TW lock Abwinden	
54	2 111,05	AT	AT	Straßen- und Eisenbahnbrücke Mauthausen	Road/Rail	8,35	66,70	D	8,35	69,00	U	510 cm Mauthausen	
55	2 094,50	AT	AT	Schleusenbrücke Wallsee-Mitterkirchen	Lock	10,07	24,00	D + U	10,07	24,00	D + U	232.33 m a. A. TW lock Wallsee	
56	2 080,82	AT	AT	Straßenbrücke Grein	Road	8,31	99,50	D + U	--	--	--	228.70 m a. A. Grein-Straßenbrücke	Height at crest: 10.47
57	2 060,42	AT	AT	Kranbrücke Schleuse Ybbs-Persenbeug	Lock	8,01	24,00	D + U	8,01	24,00	D + U	226.50 m a. A. HW lock Persenbeug	
58	2 060,15	AT	AT	Schleusenbrücke Persenbeug	Road	9,67	24,00	D + U	9,67	24,00	D + U	217.60 m a. A. TW lock Persenbeug	
59	2 043,60	AT	AT	Straßenbrücke Pöchlarn	Road	8,91	85,60	D	8,31	85,80	U	214.31 m a. A. Donaubrücke Pöchlarn	Height at crest: 10.91 (Passageway 1) and 10.38 (Passageway 2)
60	2 038,12	AT	AT	Schleusenbrücke Melk	Lock	9,89	24,00	D + U	9,89	24,00	D + U	207.71 m a. A. TW lock Melk	
61	2 034,43	AT	AT	Straßenbrücke Melk	Road	9,68	126,70	D + U	--	--	--	703 cm Melk-Straßenbrücke	Height at crest: 13.44
62	2 003,53	AT	AT	Straßenbrücke Stein - Mautern	Road	7,67	75,50	D + U	--	--	--	195.33 m a. A. Stein-Straßenbrücke	Height indicator available
63	2 001,51	AT	AT	Eisenbahnbrücke Krems	Rail	7,94	73,90	D	8,02	73,00	U	194.74 m a. A. Krems-Eisenbahnbrücke	
64	1 999,77	AT	AT	Straßenbrücke Krems	Road	8,25	108,00	D + U	--	--	--	194.58 m a. A. Krems-Straßenbrücke	Height at crest: 8.35
65	1 991,35	AT	AT	Donaubrücke Traismauer	Road	8,55	120,00	D + U	--	--	--	194.05 m a. A. Donaubrücke Traismauer	Height at crest: 11.05
66	1 979,80	AT	AT	Schleusenbrücke Altenwörth	Lock	11,26	24,00	D + U	11,26	24,00	D + U	181.24 m a. A. TW lock Altenwörth	
67	1 965,50	AT	AT	Straßenbrücke Tulln-West (Rosenbrücke)	Road	9,91	151,00	D + U	--	--	--	177.57 m a. A. Tulln-Rosenbrücke	Height at crest: 11.27
68	1 963,15	AT	AT	Straßen- und Eisenbahnbrücke Tulln	Road/Rail	7,76	76,00	D	7,90	78,00	U	177.32 m a. A. Tulln	
69	1 949,23	AT	AT	Schleusenbrücke Greifenstein	Lock	9,29	24,00	D + U	9,29	24,00	D + U	167.71 m a. A. TW lock Greifenstein	
70	1 932,62	AT	AT	Nordbrücke (Wien)	Road	8,37	65,00	U	8,12	64,50	D	627 cm Wien-Nordbrücke	Height at crest: 8.49 (Passageway 1) and 8.31 (Passageway 2)
71	1 932,57	AT	AT	Steinitzsteg formerly: Nordsteg (Wien)	Pedestrian	8,79	65,00	U	8,41	64,50	D	627 cm Wien-Nordbrücke	
72	1 931,71	AT	AT	Floridsdorfer Brücke (Wien)	Road/Tram	8,32	118,00	D + U	--	--	--	643 cm Wien-Floridsdorferbrücke	Height at crest: 9.15
73	1 931,20	AT	AT	Nordbahnbrücke (Wien)	Rail	8,12	67,00	U	8,15	65,00	D	666 cm Wien-Nordbahnbrücke	
74	1 931,17	AT	AT	U6-Brücke (Wien)	Subway	7,71	67,00	U	7,85	65,00	D	666 cm Wien-Nordbahnbrücke	
75	1 930,45	AT	AT	Brigittener Brücke (Wien)	Road	8,53	128,00	D + U	--	--	--	161.59 m a. A. Brigittenerbrücke	Height at crest: 11.22

List of Danube Bridges

Vertical bridge clearance refers to the distance (in metres) between the lowest part of the bottom edge of a bridge in the range of the entire width of the fairway channel and the highest navigable water level (HNWL 2010).
Horizontal bridge clearance refers to the width of the fairway channel at low navigable water level (LNWL).

No.	River-km	RB	LB	Name of bridge	Main use	Passageway 1			Passageway 2			HNWL at reference gauge	Notes
						(RB downstream view)			(LB downstream view)				
						Height (m)	Width (m)	Direction	Height (m)	Width (m)	Direction		
The period of reference for the calculation of HNWL and LNWL for the following bridges is 1981-2010													
76	1 928,90	AT	AT	Reichsbrücke (Wien)	Road	7,88	60,00	U	7,94	59,00	D	743 cm Wien-Reichsbrücke	Height at crest: 8.42 (Passageways 1 + 2)
77	1 925,99	AT	AT	Donaustadtbrücke (Wien)	Subway	8,24	123,00	D + U	--	--	--	847 cm Wien-Praterbrücke	Partly overlapping lanes in passageway
78	1 925,76	AT	AT	Praterbrücke (Wien)	Road	7,91	131,00	D + U	--	--	--	847 cm Wien-Praterbrücke	
79	1 924,96	AT	AT	Ostbahnbrücke (Wien)	Rail	8,03	66,00	U	7,99	65,00	D	919 cm Wien-Ostbahnbrücke	
80	1 921,05	AT	AT	Kraftwerksbrücke KW Freudenau	Lock	10,16	24,00	D + U	10,14	24,00	D + U	155.55 m a. A. TW lock Freudenau	
81	1 920,87	AT	AT	Fußgängerbrücke KW Freudenau	Pedestrian	8,92	59,00	D + U	--	--	--	155.55 m a. A. TW lock Freudenau	
82	1 917,70	AT	AT	Rohrbrücke Mannswörth	Pipeline	11,60	120,00	D + U	--	--	--	528 cm Mannswörth-Rohrbrücke	Height at crest: 13.55
83	1 914,35	AT	AT	Barbarabrücke (Schwechat)	Pipeline	11,37	120,00	D + U	--	--	--	551 cm Barbarabrücke	Height at crest: 13.03
84	1 886,25	AT	AT	Straßenbrücke Hainburg	Road	13,46	120,00	D + U	--	--	--	582 cm Hainburg-Straßenbrücke	Height at crest: 13.55
85	1 871,35	SK	SK	Most Lafranconi (Bratislava)	Road	11,03	120,00	D + U	--	--	--	645 cm Bratislava	Height at crest: 15.88
86	1 869,10	SK	SK	Most SNP (Bratislava)	Road	11,28	138,00	D + U	--	--	--	645 cm Bratislava	Height at crest: 12.12.
87	1 868,14	SK	SK	Starý most (Bratislava)	Road/Rail	10,00	100,00	D + U	--	--	--	645 cm Bratislava	
88	1 867,30	SK	SK	Most Apollo (Bratislava)	Road	11,75	150,00	D + U	--	--	--	645 cm Bratislava	150 m width between the notice marks. 210 m available between the bridge piers.
89	1 866,40	SK	SK	Prístavný most (Bratislava)	Road/Rail	11,06	128,00	D + U	--	--	--	645 cm Bratislava	
90	1 819,30	SK	SK	Lock Bridge Gabčíkovo	Lock	8,72	34,00	D + U	8,70	34,00	D + U	644 cm Medved'ov	HNWL 115,30 m a. A. at Gabčíkovo lock
91	1 806,36	HU	SK	Medve-híd/Most Medve (Medved'ov)	Road	8,51	121,00	D	9,18	80,00	U	557 cm Nagybajcs / 644 cm Medved'ov	
92	1 770,40	HU	SK	Komáromi-híd [rail]	Rail	8,83	95,40	D	8,86	94,20	U	536 cm Komárom / 588 cm Komárno	
93	1 767,80	HU	SK	Komáromi-híd [road]	Road	7,29	80,00	U	7,29	80,00	D	536 cm Komárom / 588 cm Komárno	Height at crest: 9.31 (Passageway 1) and 9.29 (Passageway 2)
94	1 718,80	HU	SK	Esztergom (Štúrovo) (Maria Valeria híd)	Road	11,37	80,00	U	11,37	100,00	D	502 cm Esztergom / 503 cm Štúrovo	
95	1 659,80	HU	HU	MO Északi (Budapest North)	Road	13,21	180,00	D + U	--	--	--	668 cm Budapest	Height at crest: 13.53
96	1 654,40	HU	HU	Újpesti-híd (Budapest)	Rail	9,50	70,00	D	9,50	70,00	U	668 cm Budapest	
97	1 651,40	HU	HU	Árpád-híd (Budapest)	Road	8,16	70,00	D	8,19	70,00	U	668 cm Budapest	Height at crest: 8.16 (Passageway 1) and 8.19 (Passageway 2)
98	1 648,80	HU	HU	Margit-híd (Budapest)	Road	9,95	60,00	D	9,95	60,00	U	668 cm Budapest	Height at crest: 9.79 (Passageway 1) and 9.94 (Passageway 2)
99	1 647,00	HU	HU	Lánchíd (Széchenyi) (Budapest)	Road	8,20	130,00	D + U	--	--	--	668 cm Budapest	Height at crest: 8.20 at a width of 80 m

List of Danube Bridges

Vertical bridge clearance refers to the distance (in metres) between the lowest part of the bottom edge of a bridge in the range of the entire width of the fairway channel and the highest navigable water level (HNWL 2010).
Horizontal bridge clearance refers to the width of the fairway channel at low navigable water level (LNWL).

No.	River-km	RB	LB	Name of bridge	Main use	Passageway 1			Passageway 2			HNWL at reference gauge	Notes
						(RB downstream view)			(LB downstream view)				
						Height (m)	Width (m)	Direction	Height (m)	Width (m)	Direction		
The period of reference for the calculation of HNWL and LNWL for the following bridges is 1981-2010													
100	1 646,00	HU	HU	Erzsébet-híd (Budapest)	Road	8,72	180,00	D + U	--	--	--	668 cm Budapest	Height at crest: 8.72 at a width of 80 m
101	1 645,30	HU	HU	Szabadság-híd (Budapest)	Road	9,54	80,00	D + U	--	--	--	668 cm Budapest	Height at crest: 9.54
102	1 644,30	HU	HU	Petőfi-híd (Budapest)	Road	9,47	80,00	D + U	--	--	--	668 cm Budapest	Height at crest: 9.47
103	1 643,10	HU	HU	Lágymányosi-híd (Budapest)	Road	9,15	60,00	D	9,15	60,00	U	668 cm Budapest	
104	1 643,10	HU	HU	Déli-híd (Budapest)	Rail	9,15	60,00	D	9,15	60,00	U	668 cm Budapest	
105	1 632,90	HU	HU	MO híd (Budapest South)	Road	10,00	100,00	D	10,00	100,00	U	668 cm Budapest	
106	1 571,60	HU	HU	Pentele-híd (Dunaújváros-Dunavecse)	Road	11,86	180,00	D + U	--	--	--	551 cm Dunaújváros	Height at crest: 13.31
107	1 560,40	HU	HU	Dunaföldvári-híd (Dunaföldvár)	Road/Rail	8,73	74,00	D	8,73	74,00	U	546 cm Dunaföldvár	
108	1 498,81	HU	HU	Szekezárdi-híd (Szent László) (Bogyszló)	Road	9,50	100,00	D	9,50	100,00	U	805 cm Baja	Height at crest: 11.55
109	1 480,22	HU	HU	Bajai-híd (Türr István) (Baja)	Road/Rail	8,09	60,00	D	8,40	60,00	U	805 cm Baja	
110	1 424,43	HR	RS	Road Bridge Bezdan - Batina	Road	9,29	120,00	D + U	--	--	--	602 cm GS Bezdan	Clearance at fairway axis: 11.07
111	1 366,63	HR	RS	Road Bridge Bogojevo - Erdut	Road	9,60	125,00	D + U	--	--	--	596 cm GS Bogojevo	Clearance at fairway axis: 11.81
112	1 366,44	HR	RS	Railroad Bridge Bogojevo - Erdut	Rail	8,59	80,00	D + U	--	--	--	596 cm GS Bogojevo	Clearance at fairway axis: 8.80
113	1 297,05	HR	RS	Road Bridge Bačka Palanka - Ilok	Road	10,13	120,00	D + U	--	--	--	578 cm GS Bačka Palanka	Clearance at fairway axis: 10.66
114	1 257,57	RS	RS	Road Bridge "Sloboda"	Road	14,16	190,00	D + U	--	--	--	573 cm GS Novi Sad	Clearance at fairway axis: 15.98
115	1 255,07	RS	RS	Road Bridge "Varadinska duga"	Road	9,73	125,00	D + U	--	--	--	573 cm GS Novi Sad	Clearance at fairway axis: 11.12
116	1 254,20	RS	RS	Road-Railroad Bridge "Žeželjev most"	Road/Rail	9,80	150,00	D + U	--	--	--	573 cm GS Novi Sad	Clearance at fairway axis: 10.01
117	1 232,17	RS	RS	Road Bridge "Beška"	Road	38,05	180,00	D + U	--	--	--	573 cm Novi Sad	Clearance at fairway axis: 43.09
118	1 176,10	RS	RS	Road Bridge "Pupinov most"	Road	10,76	150,00	D + U	--	--	--	623 cm GS Zemun	Clearance at fairway axis: 15.85
119	1 166,63	RS	RS	Road-Railroad Bridge "Pančevacki most"	Road/Rail	9,83	100,00	D	9,37	100,00	U	623 cm GS Zemun	Clearance at fairway axis D: 9.83; U: 9.55
120	1 112,90	RS	RS	Pipeline Bridge Smederevo	Pipeline	12,19	120,00	D + U	--	--	--	680 cm GS Smederevo	Clearance at fairway axis: 13.44
121	1 112,10	RS	RS	Road Bridge Smederevo - Kovin	Road	8,44	150,00	D + U	--	--	--	680 cm GS Smederevo	Clearance at fairway axis: 11.36
122	1 045,12	RO	RO	Road bridge Moldova Veche	Road	23,71	150,00	D + U	--	--	--	Impounded water level Iron Gate I	
123	942,90	RS	RO	Road/crane bridge (Đjerdap I/Portile de Fier I)	Lock	13,50	34,00	D + U	10,00	34,00	D + U	Impounded water level Iron Gate I	Bridge can be lifted near right bank from 10.00 to 13.50
124	942,60	RO	RO	Maintenance bridge (Đjerdap I/Portile de Fier I)	Lock	--	--	--	10,00	34,00	D + U	Impounded water level Iron Gate I	Bridge only on left bank

List of Danube Bridges

Vertical bridge clearance refers to the distance (in metres) between the lowest part of the bottom edge of a bridge in the range of the entire width of the fairway channel and the highest navigable water level (HNWL 2010).

Horizontal bridge clearance refers to the width of the fairway channel at low navigable water level (LNWL).

No.	River-km	RB	LB	Name of bridge	Main use	Passageway 1			Passageway 2			HNWL at reference gauge	Notes
						(RB downstream view)			(LB downstream view)				
						Height (m)	Width (m)	Direction	Height (m)	Width (m)	Direction		
The period of reference for the calculation of HNWL and LNWL for the following bridges is 1981-2010													
125	863,55	RO	RO	Road bridge (Portile de Fier II)	Lock	--	--	--	17,70	34,00	D + U	Impounded water level Iron Gate II	Lock at left bank
126	863,00	RS	RS	Road bridge (Đjerdap II)	Lock	13,87	34,00	D + U	--	--	--	Impounded water level Iron Gate II	Lock at right bank
127	796,10	BG	RO	Bridge Vidin - Calafat/Podul Calafat-Vidin	Road/Rail	--	--	--	21,79	148,00	D + U	671 cm Calafat	Passageway 1 will presumably be available after dredging in 2020, the height and reference is related to the Romanian reference system
128	488,70	BG	RO	Road and rail bridge Giurgiu-Rousse	Road/Rail	13,91	150,00	D	13,91	150,00	U	707 cm Giurgiu	3rd passageway available (width: 76.00, height: 14.40 / 21.82), the height and reference is related to the Romanian reference system
129	300,07	RO	RO	Road and rail bridge Cernavodă	Road/Rail	24,99	150,00	D + U	--	--	--	604 cm Cernavodă	
130	300,00	RO	RO	Rail bridge Cernavodă	Rail	24,99	150,00	D + U	--	--	--	604 cm Cernavodă	
131	237,80	RO	RO	Road bridge Vadu Oii - Giurgeni	Road	17,70	120,00	D	15,20	100,00	U	644 cm Hârșova	Height at crest: 20.70 (Passageway 1) and 19.35 (Passageway 2)

PORT ENTRANCES

The period of reference for the calculation of HNWL and LNWL for the following bridges is 1981-2010													
1	2 127,16	AT	AT	Port of voestalpine Linz	Rail/Pipeline	6,72	60,00	D + U	--	--	--	251.50 m a. A. Linz-VOEST-Hafen	Height at crest: 7.08
2	1 998,00	AT	AT	Port of Krems	Road	8,51	23,00	D + U	--	--	--	194.30 m a. A. Thallern	Height at crest: 8.76
3	1 920,10	AT	AT	Port of Wien-Freudenau [road]	Road	8,24	34,00	D + U	--	--	--	155.55 m a. A. TW lock Freudenau	Height at crest: 9.54
4	1 920,45	AT	AT	Port of Wien-Freudenau [rail]	Rail	9,96	20,00	D + U	--	--	--	155.34 m a. A. Donaukanalmündung	
5	1 916,80	AT	AT	Oil port Lobau	Pipeline	11,34	44,00	D + U	--	--	--	543 cm Hafenzufahrtsskanal	
6	1 866,25	SK	SK	Port of Bratislava (Prístavný most)	Road/Rail	11,06	50,00	D + U	--	--	--	645 cm Bratislava	
7	1 865,40	SK	SK	Port of Bratislava-Pálenisko	Pipeline	11,88	100,00	D + U	--	--	--	645 cm Bratislava	
8	1 767,00	SK	SK	Port of Komárno	Road	5,69	40,00	D + U	--	--	--	588 cm Komárno	Height at crest: 7.67

List of Danube Bridges

Vertical bridge clearance refers to the distance (in metres) between the lowest part of the bottom edge of a bridge in the range of the entire width of the fairway channel and the highest navigable water level (HNWL 2010).

Horizontal bridge clearance refers to the width of the fairway channel at low navigable water level (LNWL).

No.	River-km	RB	LB	Name of bridge	Main use	Passageway 1			Passageway 2			HNWL at reference gauge	Notes
						(RB downstream view)			(LB downstream view)				
						Height (m)	Width (m)	Direction	Height (m)	Width (m)	Direction		
The period of reference for the calculation of HNWL and LNWL for the following bridges is 1981-2010													

BORCEA SIDEARM

The period of reference for the calculation of HNWL and LNWL for the following bridges is 1981-2010													
1	42,30	RO	RO	Rail bridge Fetești-Cernavodă	Rail	11,65	100,00	U	11,20	100,00	D	639 cm Călărași	
2	42,22	RO	RO	Road/rail Fetești-Cernavodă	Road/Rail	11,65	100,00	U	11,20	100,00	D	639 cm Călărași	

DANUBE-BLACK SEA CANAL

Minimum height under the seven bridges of the Danube-Black Sea Canal is 16.50 m above highest navigable water level.

ABBREVIATIONS

No. = consecutive number RB = situated close to or on the right bank LB = situated close to or on the left bank D = for vessels headed downstream U = for vessels headed upstream HW = headwater of a barrage or lock TW = tailwater of a barrage or lock
n. s. = not specified a. A. = above Adria

SOURCES

Wasserstraßen- und Schifffahrtsamt Regensburg, viadonau, Dopravný úrad, Észak-Dunántúli Vízügyi Igazgatóság, Agencija za Vodne Putove, Ploput, Autoritatea Navală Română, Danube Commission, electronic navigational charts, WESKA - Europäischer Schifffahrts- und Hafenkalender

EXCLUSION OF LIABILITY

viadonau does not assume liability for the correctness and completeness of the information provided. Any claim of liability based on this bridge data provided by viadonau as service feature is, by any means whatsoever, excluded and void.

1-41: heights of passageways are rounded down to 0.05 m

type = main use

class = UNECE/ECMT-waterway class of the section, in which the bridge is located